

ZKB204

2D Barcode Scanning Platform



ZKB204 scanning platform, which integrates with powerful scanning efficiency, advanced image scanning technology, beautiful and durable appearance, It is the first-choice equipment of you to improve your work efficiency!

Features

- Excellent 1D/2D barcode reading performance
- Good athletic tolerance
- IP52 dustproof
- 1.2m drop resistance
- Infrared speed sensing
- Rich interface
- Green low power

Application Scenarior

Apply in express, supermarket cash register, clothing store inventory, warehouse inventory and other industry.

Specifications

| Performance Parameters | |
|--------------------------|--|
| Imaging Sensor | CMOS |
| Symbol Contrast | ≥30% |
| Interface | USB HID-KBW, USB virtual port, USB HID-POS, TTL-232, RS-232 |
| Symbologies | 1D:Code128, UCC/EAN-128, AIM-128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5, Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, GS1-DataBar (RSS), (RSS-14, RSS- Limited, RSS-Expand) 2D:PDF417, QR Code (QR1/2, Micro), Data Matrix (ECC200, ECC000, 050, 080, 100, 140) |
| Scan Angle | Pitch ±50°@ 0°Roll and 0° Skew |
| | Roll ±360°@ 0°Pitch and 0° Skew |
| | Skew ±60°@ 0°Roll and 0° Pitch |
| Physical Parameters | |
| Dimensions | 106mm × 111mm × 155mm |
| Weight | 320g |
| Notification | Beep, LED indicator |
| Current | Operating 240mA |
| | Standby 190mA |
| Environmental Parameters | |
| Operating Temperature | -20℃ ~+50℃ (-4°F~122°F) |
| Storage Temperature | -40℃ ~+80℃ (-40°F~176°F) |
| Humidity | 5%~95% (non-condensing) |
| ESD | ±14 kV (air discharge) , ±8 kV (direct discharge) |
| Drop | 1.2m drops to concrete(for six sides,one drop per side) |
| Sealing | IP 52 |
| Certifications | |
| | FCC Part15 Class B, CE EMC Class B |

