

F19

Fingerprint Standalone Access Control



F19 is an innovative biometric fingerprint reader for access control application. offering unparalleled performance by using an advanced algorithm for reliability, precise and excellent matching speed. The F19 features the fastest commercial-based fingerprint matching algorithm and ZK high performance, high image quality, infrared detection fingerprint sensor. The device offers flexibility to be installed standalone or with any third party access control panels that support standard wiegand signal. All the operation can be done on the TFT LCD color screen. The fingerprint image will be displayed on it. That will guide user to put finger on proper position and increase recognition rate. TCP/IP and RS485 are available that the device can be used in different network.



TFT Color Screen

- Audio-visual indication for acceptance and rejection of valid/invalid fingerprints
- More simple and convenient operation



Slim and Elegant Design

- Streamlined and slim design for narrow spaces



Fast and Accurate Algorithm

- User recognition in 1 second
- Stores 3,000 fingerprint templates and 30,000 transactions



Easy Installation and Connectivity

- Wiegand input & output
- Network interface by TCP/IP or RS485



Full Access Control Features

- Webserver
- Anti-passback
- Access control interface for 3rd party electric lock, door sensor, exit button, alarm and doorbell




Easy Operation and Management

- Works with computer
- Buzzer, 4x4 keypads and doorbell
- Built-in serial and ethernet ports
- Built-in USB port allows for manual data transfer

Specifications

Display	TFT LCD Color Screen
Fingerprint Capacity	3,000
Card Capacity	5,000 (Optional) ID /Mifare card
Transaction Capacity	30,000
Sensor	ZK Optical Sensor
Algorithm Version	ZK Finger V9.0&10.0
Communication	RS232/485, TCP/IP, USB-host
Access Control Interface	3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell
Wiegand Signal	Input, Output
Functions	Webserver, Anti-passback
Power Supply	12V DC, 3A
Operating Temperature	0 °C- 45 °C
Operating Humidity	20%-80%
SDK and Software	ZKAccess3.5
Dimension(WxDxH)	87×195×42.5mm

Configuration



Optional Accessories



Electric Lock



Alarm



Sensor



FR1200



RFID Reader



Exit Button



ZKTeco Middle East
www.zkteco.me
 E-mail: zk_me@zkteco.com

© Copyright 2016. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

