

# Card And Tag

## ZKLT-E



- ID Location Tag installed at Checkpoints for guard tour monitoring system

## ZKLT-M



- Mifare Location Tag installed at Checkpoints for guard tour monitoring system

## ID card(thin)



- 125kHz Proximity Card
- Read only

## ID card(Thick)



- 125kHz Proximity Card
- Read only

## ID card(long range)



- 125kHz Proximity Card
- Read only
- Suitable for KR1000 for 60cm reading range

## Mifare card(S70)



- 13.56Mhz Mifare One Card
- Standard MF1 S70(4 Kbyte) EEPROM

## Mifare card(S50)



- 13.56Mhz Mifare One Card
- Standard MF1 S50(1 Kbyte) EEPROM

## HID Card(thin)



- 125kHz HID proximity card

## HID Card(thick)



- 125kHz HID proximity card

## TAG-03(ID)



- 125KHz Proximity TAG

## TAG-03(Mifare S50)



- 13.56MHz Proximity TAG

## TAG-03(Mifare S70)



- 13.56MHz Proximity TAG

## TAG-04



- Watchband 125KHz Proximity TAG
- Color: Blue
- Diameter:  $\Phi 65$ mm

## NFCTag



- Frequency: 13.56MHZ
- Dimension: Tag  $\Phi 25$ , antenna  $\Phi 19$
- storage capacity: 168byte



ZKTeco Middle East  
E-mail: [zk\\_me@zkteco.com](mailto:zk_me@zkteco.com)  
[www.zkteco.me](http://www.zkteco.me)

© Copyright 2014. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

