

# Quick Start Guide

---

**Model: TL300Z**

Version: 1.0

# How to pair the Gateway and Smart Lock with the ZSmart App?

## Step 1. Download the ZSmart App

- 1 Search for the "ZSmart" App in iOS App Store or Google Play Store, or scan the QR code to download the App.
- 2 Open the "ZSmart" App, register and sign in to the account.



## Step 2. Add the Gateway

- 1 Plug the Gateway into the outlet using the provided Power Adapter. Wait for a few seconds until the **red LED blinks rapidly**.
- 2 Open the ZSmart App. Tap the "+" button on the upper right corner of the interface, and then select "**Smart Lock / Wireless Gateway**" category.
- 3 Follow the on-screen instructions to connect the Gateway to 2.4GHz Wi-Fi network and complete the setup.

**Note:** The default pairing mode is **EZ Mode**. If the red LED blinks slowly, press and hold the **Reset** button for 5 seconds to make the red LED blink rapidly.

## Step 3. Add the Smart Lock

- 1 Tap the "+" button on the upper right corner, and then select "**Smart Lock / TL300Z**" category to add to the Gateway.
- 2 Follow the on-screen instructions, and tap the "**Confirm**" button first.
- 3 Then program the Network Settings on the lock. The steps are as follows: Activate the lock -> Press the **0** and **#** keys to access the menu -> Verify the Administrator's identity -> Press the **8#** and **3#** keys first, and then **1** and **#** keys.
- 4 Once you see the message "**Device added successfully**" on the mobile app, tap the "**Done**" button to complete the setup.



*Now, you can manage the lock from anywhere via ZSmart App!*

*¡Ahora, puede administrar la cerradura desde cualquier lugar a través de la aplicación ZSmart!*

*Agora, você pode gerenciar a fechadura de qualquer lugar via App ZSmart!*

ZKTeco Industrial Park, No. 26, 188 Industrial Road,

Tangxia Town, Dongguan, China.

Phone :+86 769-82109991

Fax :+86 755-89602394

[www.zkteco.com](http://www.zkteco.com)

