

ZKP5804

Thermal Receipt Printer



ZKP5804 is a low-cost and high-quality thermal printer with a lightweight, compact design. This thermal receipt printer has a fast printing speed (90mm/s printing speed) and equips with an easy paper-loading structure. As a result, ZKP5804 is suitable for various commercial retail POS systems.

Features

- Unique appearance design, acrylic panel design
- 90mm/s low operation noise, high speed printing
- Low-cost with high-quality printing
- Easy paper loading structure, easy to use and maintain
- Compatible with ESC/POS printing commands

Applications



Fashion Chain Stores



Supermarkets



Restaurants

Specifications

Color	Black and Gray, (White, optional)
Print Method	Direct thermal
Paper Width	57.5±0.5mm
Print Width	48mm
Paper Roll Diameter	Max 60mm
Print Resolution	384 dots/ line (Adjustable by command)
Printing speed	90 mm/s
Interface	USB
Line Spacing	3.75mm (Adjusted by command)
Character Set	Alphanumeric; International
Column Number	Font A: 42 columns or 48 columns
Character Size	ANK Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
Extension Character Sheet	PC437 (European Standard)/ (Katakana)/ PC850(Multilingual) / PC860 (Portugal)/ PC863 (Canadian)/PC865 (Nordic)/ (West Europe)/ (Greek)/ (Hebrew)/ (East Europe)/ (Iran)/ (WPC1252)/ PC866 (Cyrillic#2)/ PC852 (Latin2)/ (PC858)/ (IranII)/ (Latvian)/ (Arabic)/ (PT1511251)
Power Adapter	Input: AC 100-240V / 50-60 Hz; Output: DC 12V/3A
Printer Input	DC 12V/3A
Cash Drawer	DC 12V/1A
Printer Head Life	50Km
Dimensions(D*W*H)	120*105*102 (mm)
Net Weight	0.35 Kg
Packing Weight	0.70 Kg
Operation Temperature	0°C to 45°C
Storage Temperature	-10°C to 60°C
Operation Humidity	10% to 80%RH
Storage Humidity	10% to 90%RH
Certifications	CE & FCC & RoHS

