

PT-DA294K2

IR 4MP H.265 IP Camera



- Support ID, IP, DDNS Server
- Support Mobile View (IOS, Android)
- Support Web Access
- Support Web, CMS
- Support ONVIF
- Support Auto Electric Shutter

Specifications

Product Model	PT-DA294K2
Video Compression	H.265/H.264
Sensor	OV4689 CMOS
Light-sensing surface area	1/3-inch
Resolution	4.0MP
Definition	2592(H)*1520(V)
Min. illumination	Color: 0.01Lux@(F1.2,AGC ON),0 LUX with IR B&W: 0.001Lux@(F1.2,AGC ON),0 LUX with IR
Lens	4mm fixed lens(6/8/12 optional)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP HTTPS, SIP, 802.1x, IPv6 optional
Ethernet	RJ45 10M/100M adaptive ethernet interface
Shutter	1/50(1/60)s to 1/10,000s
IR Distance	2*Array LED: 20m
Power Supply	DC12V±10%
Working Environment	-10 °C- 60 °C, Less than 90%RH
Dimension(Color Box)	130mm*130mm*102mm
Gross/Net Weight	0.28kg/0.2kg

