

PT-BA294K2/294K4

High Definition Waterproof IP Cameras



Features:

- Support ONVIF
- Support ID, IP, DDNS server
- Support Web Access
- Mobile view (IOS, Android)

Specifications

Model	PT-BA294K2	PT-BA294K4
Sensor	OV4689 cmos	
Light-sensing surface area	1/3-inch	
Resolution	4.0MP	
Definition	2592(H)*1520(V)	
Video Frame	50Hz:4M(2592*1520)@15fps, 3M(2048*1536)@25fps 60Hz:4M(2592*1520)@15fps, 3M(2048*1536)@30fps	
Video Compression	H.265/H.264	
Min. illumination	Color:0.01Lux@ (F1.2,AGC ON), 0 LUX with IR B&W:0.001Lux@ (F1.2,AGC ON), 0 LUX with IR	
Lens	4mm fixed lens (6/8/12mm optional)	
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP (HTTPS, SIP, 802.1x, IPv6optional)	
Ethernet	1*RJ45 10M/100M	
Shutter	1/50(1/60)s to 1/10,000s	
IR Distance	2*Array LED: 20m	4*Array LED: 50m
Power Supply	DC12V±10%	
Working Environment	-10 °C- 60 °C, Less than 90%RH	
Gross/Net Weight	0.64KG/0.5KG	
Dimension(color box)	230mm*130mm*117mm	

