

# BT-BA10K2/13K2/13K4/20K4

## High Definition IR IP Cameras



### Features:

- Support Onvif2.4, P2P function and mobile view through main stream NVR
- 3D DNR, 8\*ROI Area, Stable Snapshot
- Motion Detection

### Specifications

Model	BT-BA10K2	BT-BA13K2	BT-BA13K4	BT-BA20K4
Sensor	Progressive scan CMOS sensor			
Light-sensing area	1/4-inch	1/3-inch	1/3-inch	1/2.7-inch
Resolution	1.0MP	1.3MP	1.3MP	2.0MP
Definition	1280(H)x720(V)	1280(H)x960(V)	1280(H)x960(V)	1920(H)x1080(V)
Video Frame	50Hz: 25fps    60Hz: 30fps;			
Video Compression	H.264			
Min. illumination	Color: 0.05Lux@(F1.2), Black: 0.01Lux@(F1.2), 0 LUX with IR			
Lens	4mm@F1.8 (6/8/12mm optional)			
Protocol	TCP/IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP			
Working Environment	-10 °C- 60 °C, Less than 90%RH			
Shutter	Auto			
Infrared Resection	IR-CUT			
IR Distance	20m	20m	50m	50m
Power Supply	DC12V±10%			
Operating Temperature	-10 °C- 50 °C			
Net/Gross Weight	0.64KG/0.5KG			
Dimension(color box)	230mm*130mm*117mm			

